

Thermatek Harness and Lanyard

Product Specifications



Application

Specially designed for high-heat applications e.g. for use in the welding industry.

Thermatek Harness, p/ns: 10129398 small, 10129399 medium, 10129400 large

| FEATURES | |
|---|---|
| Kevlar/Nomex webbing | For flame, heat and cut resistance |
| Bright, contrasting colors of webbing and stitching | Allows for easier inspection |
| Kevlar stitching | Increases product life |
| A rip stitch indicator | Alerts users that the harness has been involved in a fall |
| A back fall arrest attachment | For safe connection to fall protection system |
| Qwik-Fit buckles | For easy connection of harness |
| Fully adjustable leg, chest and shoulder straps | For perfect fit |
| Available in small, medium and large sizes | Fits a wide range of body types |
| MATERIALS | |
| Web | Kevlar/Nomex, 45 mm, Black with Natural Edges |
| Hardware | |
| <i>D-Ring</i> | Alloy steel |
| <i>Buckles</i> | Galvanized Steel |
| Thread | Kevlar |
| Plastic Parts | Santoprene |
| Labels | Tyvek |
| TECHNICAL | |
| Web Minimum Breaking Strength | 44 KN |
| Dorsal D-ring Min. Breaking Strength | 22 KN |
| CERTIFICATION | |
| Certified to | EN 361:2002 |



Thermatek Lanyard, p/n 10101888

| FEATURES | |
|--|-----------------------------------|
| A Tuffweld protective cover over the energy-absorber | Fire resistant material |
| Kevlar back-up strap inside the energy-absorber | Resistant to charring and burning |
| Cable | 6 mm plastic coated steel |
| Length | 1,8 m |
| Snap-hooks | 2 x 19 mm |
| MATERIALS | |
| Cable | Steel Cable |
| Shock Absorber | |
| <i>Fabric Cover</i> | Kevlar/Nomex blend |
| <i>Thread</i> | Kevlar |
| Connecting Hardware | |
| <i>Snaphook</i> | Forged steel |
| TECHNICAL | |
| Maximum Arresting Force | 6 kN |
| CERTIFICATION | |
| Certified to | EN 355:2002, EN 354:2010 |



Thermatek Anchorage Strap, p/n 10103221

| FEATURES | |
|--|--------------------------------|
| Contrasting colours of webbing and stitching | Allow for easier inspection |
| Includes replaceable wear pad | Protects webbing from abrasion |
| Length | 1,5 m |
| MATERIALS | |
| Web | Kevlar |
| Thread | Kevlar |
| Connecting Hardware | |
| <i>D-Ring</i> | Alloy steel |
| TECHNICAL | |
| Strap Minimum Breaking Strength | 22 KN |
| Maximum Arresting Force | 6 kN |
| CERTIFICATION | |
| Certified to | EN 795:1996 |

