

Vented helmet - Functional and stylish



## V-Gard 200 vented Safety Helmet

Key features and benefits

- UV stabilised ABS helmet shell offers good resistance to scratches
- Lightweight
- Stylish design
- Short peak for improved upward vision
- Effective ventilation system with larger holes on the upper part: most ventilated helmet of the market with 445 mm<sup>2</sup> of ventilation holes
- Limited rain gutter
- Provides lateral crushing protection
- Standard slots to easily attach MSA visors and/or ear muffs
- 2- or 3-point chinstraps available
- 9 shell colours: white, yellow, red, blue, green, black, orange, fluo orange, fluo yellow
- Build UK Approved Colour
- Options : MSA LOGO EXPRESS(R) pad printing on all helmet sides; retro-reflective stickers; individual naming

- Lifetime: 3 years storage, +5 years service time; MSA delivers stickers to note date of first use and stick to inside shell
- ELECTROSTATIC-INERIS certified (testing according to EN 13463-1). Suitable for use in ATEX environments hazardous zones 1, 2,20, 21, 22
- 4 suspensions available: -Push-Key with slide adjustment and sweat-wicking foam

sweatband -Push-Key with slide adjustment and wipeable PVC sewn in

sweatband

-Fas-Trac<sup>®</sup> III with wheel ratchet and sweat-wicking foam sweatband

-Fas-Trac<sup>®</sup> III with wheel ratchet and wipeable PVC sewn in sweatband

**Vented helmet** - Functional and stylish



### MSA Suspensions - General features and benefits

- Overhead straps made of woven polyester providing high comfort and long term, consistent shock absorption performance
- Ensures consistent performance and comfort level even under the influence of moisture or low temperatures
- Sophisticated 4 point attachment: good positioning, stability and better air circulation
- Ideal positioning of the harness through height and length adjustment: perfect for use with face masks
- Self-adjusting textile crown straps for fast height adjustment and comfortable fit



## MSA Push-Key suspension

Features and benefits

#### • EASE OF USE:

- This is the fastest sliding suspension on the market: simple push to loosen, squeeze to tighten

- Can be adjusted with one hand even when worn

#### • SURE FITTING:

 It offers greater retention capacity than competitive sliding suspensions because it's so much easier to select the best adjustment position

#### • ADJUSTABILITY:

- 2 levels of nape adjustment for fitting comfort
- Designed to avoid interference with other PPE such as ear muffs

#### • SWEATBAND COMFORT:

 2 different options: sewn in PVC perforated wipeable or sweatwicking foam

### MSA Fas-Trac® III suspension

Features and benefits

#### BALANCE & STABILITY:

- Lower nape strap improves retention: Helmets stay on when leaning over

- Adjusts for a custom fit to the back of the head

#### HEADBAND COMFORT:

The comfort pad by separating the ratchet from the head, cradles the head increasing comfort and cooling airflow
 Prevents hair from getting pulled

### EASE OF USE:

- Ratchet offers smooth rotation: reduced effort to turn
- Easy grip knob adjustable even with gloves on

#### • ADJUSTABILITY:

- Three levels of nape height adjustment giving superior nape fit
- Avoids interference with other PPE such as ear muffs
- SWEATBAND COMFORT:

- Largest sweatband surface area on the market covers more of the headband and user's forehead for increased comfort

 2 different sweatband options: sewn in PVC perforated wipeable or sweat-wicking washable foam(breathable fabric allows direct air permeation)

 Replaceable foam sweatband can be attached over the existing sweatband without demounting the suspension

Also available Terry cotton washable sweatband that can be used over both sewn in PVC or replaceable foan sweatbands for increased user comfort



### MSA**safety**.com

**Vented helmet** - Functional and stylish



## Technical Specifications

|  | 5 (Acrylonitrile Butadiene Styrene), UV stabilized, Non-Vented  |  |  |  |
|--|---|--|--|--|
| Weight 260   |   |  |  |  |
|  | 260g  |  |  |  |
| Suspensions  |   |  |  |  |
| Pus<br>Fas-  | Push-Key with slide adjustment and sweat-wicking foam sweatband: 66 g<br>Push-Key with slide adjustment and wipeable PVC sewn in sweatband: 70 g<br>Fas-Trac <sup>®</sup> III with wheel ratchet and sweat-wicking foam sweatband: 89 g<br>Fas-Trac <sup>®</sup> III with wheel ratchet and wipeable PVC sewn in sweatband: 91 g  |  |  |  |
| Webbing Blac   | Black Polyester (PET), double straps, 4 points  |  |  |  |
| PVC<br>Pus<br>in co<br>Fas<br>PVC<br>Fas                               | <ul> <li>sh-Key with wipeable sewn in PVC sweatband and Polyurethane (PU) internal foam. Nontoxic</li> <li>C in contact with the head.</li> <li>sh-Key with sweat-wicking Polyurethane (PU) internal grey foam and grey Polyamide (PA) finish contact with the head</li> <li>Frac<sup>®</sup> III with wipeable sewn in PVC sweatband and Polyurethane (PU) internal foam. Nontoxic</li> <li>C in contact with the head.</li> <li>Frac<sup>®</sup> III with sweat-wicking Polyurethane (PU) internal grey foam and grey Polyamide (PA) finish contact with the head.</li> <li>Frac<sup>®</sup> III with sweat-wicking Polyurethane (PU) internal grey foam and grey Polyamide (PA) finish contact with the head.</li> </ul> |  |  |  |
| Fas-   | -Trac <sup>®</sup> III: Polypropylene (PP)  |  |  |  |
| Headband Pus   | sh-Key: Low Density Polyethylene (LDPE)   |  |  |  |
| <b>Clips</b> Grey  | y Polypropylene (PP)  |  |  |  |
| Comfort pad (Fas-Trac® III)  | v Density Polyethylene (LDPE)   |  |  |  |
|  | <b>Fas-Trac® III:</b> (Ratchet): Polyoxymethylene (POM), Polypropylene (PP) and Polyamide (PA)<br><b>Push-Key:</b> (Button) : Polyoxymethylene (POM)  |  |  |  |
| <b>Size</b> 52-6   | 64 cm   |  |  |  |
| Metal parts No   |   |  |  |  |
| Approvals  |   |  |  |  |
| Show   | tified by European Notified Body UTAC (0069) according to: EN 397: 2012<br>ock absorption, resistance to penetration, flame resistance, chinstrap anchorage<br>y low temperature / -30°C, electrical insulation / 440 V AC , Lateral Deformation / LD   |  |  |  |
| Other standards Cert<br>Cert<br>- Inc<br>Dust<br>Gas:<br>- Mii<br>*Cau | tified by INERIS to EN 13463-1: 2001 for safe use in ATEX areas* (ELECTROSTATIC-INERIS testing):<br>tificate n°29406<br>dustry:<br>st: hazardous zones 20, 21, 22 (all zones)<br>s: zones 1 and 2 with gas group IIA (propane)<br>ines: any type of extraction and any depth<br>iution:when working in an ATEX area operatives must be fully equipped with appropriate PPE eg.<br>sipative shoes (earth resistance less than 1.108Ω), not just suitable industrial helmets!   |  |  |  |
| Lifetime guidelines  |   |  |  |  |
| or an<br>expo  | <b>3 years</b> from shell injection date (helmet packed in proper condition, not exposed to light, chemical or any type of pollution). Store in a proper storage bag and/or in a closed cabinet to avoid extended exposure to sunlight, cold, humidity, exhaust fumes, etc. If the helmet has been stored more than 2 years, deduct the extra storage time from the recommended helmet's service life.  |  |  |  |
| Service life (in addition to the storage time) 5 ye (sup               | ears from actual starting date of use MSA recommends writing the date of first use onto a sticker oplied with each helmet) and then sticking into the shell.This is normally the point at which vice life starts  |  |  |  |
|  | place when damaged or contaminated , or as required for hygienic reasons  |  |  |  |

**Vented helmet** - Functional and stylish



## Packaging

|                         | Description   |  |  |
|-------------------------|---|--|--|
| Individual (sales unit) | One helmet in a protective plastic bag printed with instructions, 1 tab suspensions fitted or |  |  |
|                         | 4 tabs suspensions fitted (GVxxx-xxAxxxx-xxx)   |  |  |
| Box                     | Minimum order quantity: 20 helmets with EAN code on the box                                   |  |  |
|                         | Box size: 706x586x455 mm (one tab fitted) or 720x610x460 mm (4 tab fitted)                    |  |  |
| Pallet                  | 200 helmets (10 boxes of 20 helmets)  |  |  |
|                         | Pallet size: 1200 x 730 x 1980 mm   |  |  |

## Ordering Information

| Colors      | RAL Code                              | V-Gard 200 NV PK<br>PVC sweatband   | V-Gard 200 NV PK<br>foam sweatband | V-Gard 200 NV FTIII<br>PVC Sweatband | V-Gard 200 NV FTIII<br>foam sweatband |  |
|-------------|---------------------------------------|---|------------------------------------|--------------------------------------|---------------------------------------|--|
| White       | RAL 9003                              | GV611-00A0000-000   | GV613-00A0000-000                  | GV612-00A000-000                     | GV619-00A0000-000                     |  |
| Yellow      | RAL 1018                              | GV621-00A0000-000   | GV623-00A0000-000                  | GV622-00A000-000                     | GV629-00A0000-000                     |  |
| Red         | RAL 3020                              | GV631-00A0000-000   | GV633-00A0000-000                  | GV632-00A000-000                     | GV639-00A0000-000                     |  |
| Green       | RAL 6016                              | GV641-00A0000-000   | GV643-00A0000-000                  | GV642-00A000-000                     | GV649-00A0000-000                     |  |
| Blue        | RAL 5022                              | GV651-00A0000-000   | GV653-00A0000-000                  | GV652-00A000-000                     | GV659-00A0000-000                     |  |
| Orange      | RAL 2008                              | GV661-00A0000-000   | GV663-00A0000-000                  | GV662-00A000-000                     | GV669-00A0000-000                     |  |
| Black       | RAL 9004                              | GV681-00A0000-000   | GV683-00A0000-000                  | GV682-00A000-000                     | GV689-00A0000-000                     |  |
| Fluo Orange | RAL 2005                              | GV691-00A0000-000   | GV693-00A0000-000                  | GV692-00A000-000                     | GV699-00A0000-000                     |  |
| Fluo Yellow | RAL 1026                              | GV6A1-00A0000-000   | GV6A3-00A0000-000                  | GV6A2-00A000-000                     | GV6A9-00A0000-000                     |  |
| Part No.    | Description                           |   |                                    |                                      |                                       |  |
| 10162752    | Fas-Trac <sup>®</sup> III suspension  | Fas-Trac® III suspension with ratchet and sewn in PVC sweatband                       |                                    |                                      |                                       |  |
| 10162755    | Fas-Trac <sup>®</sup> III suspension  | Fas-Trac® III suspension with ratchet and replaceable, washable, foam sweatband GVxx9 |                                    |                                      |                                       |  |
| 10162507    | Push-Key suspension wi                | Push-Key suspension with slide adjustment and sewn in PVC sweatband GVxx1             |                                    |                                      |                                       |  |
| 10162508    | Push-Key with slide adju              | Push-Key with slide adjustment and replaceable foam sweatband                         |                                    |                                      |                                       |  |
| 10153518    | Fas-Trac <sup>®</sup> III foam sweath | Fas-Trac® III foam sweatband (10 pcs) – replacements for 10162755 or GVxx9 or over    |                                    |                                      |                                       |  |
| 3335612-SP  | Push-Key foam sweatba                 | Push-Key foam sweatband (10 pcs) – replacements for 10162508 or GVxx3                 |                                    |                                      |                                       |  |
| 696688      | Terry cotton (Terri-Band)             | Terry cotton (Terri-Band) sweatband (10 pcs) – for use over sewn in PVC sweatband     |                                    |                                      |                                       |  |



| Other accessories and options | Ask for our detailed data-sheets      |
|-------------------------------|---------------------------------------|
| Options                       | Lamp brackets                         |
| Options                       | MSA LOGO EXPRESS® pad printing on all |
|                               | helmet sides                          |
| Accessories or Options        | Chinstraps                            |
| Accessories or Options        | High visibility stickers              |
| Accessories                   | Helmet mounted ear-muffs              |
| Accessories                   | Individual naming                     |
| Accessories                   | Frame and visors                      |
| Accessories                   | Winter liners                         |
| Accessories                   | Cooling liners                        |
| Accessories                   | Neck curtains                         |

