

Bone Conductive Microphone Headset, GALLET F1XF helmet, NEXUS 4, ATEX

Specification	Description
Overview	Communication headset for integration in GALLET F1XF helmet
	One or two loudspeakers, in housing with mounting clips
	Bone conductive microphone, inserted in the front headband padding or in the suspension (pocket delivered with the headset).
	Coiled downlead Cable with NEXUS type (7.1 mm jack, 4 pole) connecting plug
Interoperability	Operates with various Push-to-Talk (PTT) modules, such as MSA HandyCom, enabling connection to the PMR radio. Connection through a NEXUS type plug
Technical Specifications	✓ Microphone: Accelerometer, 100 Hz – 10 kHz, Sensitivity 1 V / 0,5G
	\checkmark Loudspeaker: 32 Ω , 20 Hz – 3 kHz, max power 100 mW
	✓ Down lead Cable: Fire retardant, shielded cable
	✓ Housing: Polyamide (PA6), Fire resistant (V0)
	✓ Operation Temperature: -20 C to +65 C, humidity < 98%
Weight	✓ Standard version (1 speaker): 60 ± 10g
	✓ Premium version (2 speakers): 85 ± 10g
Testing & Approvals	✓ EMC performance: ESD/EMI: 10 V/m
	✓ Ingress Protection testing: IP56 (tested inside the helmet)
	✓ ATEX/IECEX: II 2 G Ex ib IIC T4 Gb
	Before using ATEX/ IECEX headsets in explosive environments, ensure ATEX/ IECEX headset parameters meet the PTT/ RSM ATEX/ IECEX parameters requirement
Ordering Information	GAY10212232116000X – Headset, GALLET F1XF, Bone conductive Microphone, 1 Speaker, Nexus 4 standard wiring
	GAY10103232126000X – Headset, GALLET F1XF, Bone conductive Microphone, 2 Speakers, Nexus 4 standard wiring
	GAY10103232316000X - Headset, GALLET F1XF, Bone conductive Microphone, 1 Speaker, Nexus 4 NATO UK wiring
	GAY10103232326000X - Headset, GALLET F1XF, Bone conductive Microphone, 2 Speakers, Nexus 4 NATO UK wiring



Headset, 1 speaker



Headset, 2 speakers



Headset mounted inside helmet (chinstrap not shown)



Bone conductive sensor



Yellow disassembly lever



Connecting NEXUS plug, headset to PTT